

technical data sheet

PennWhite Print Solutions Ltd, Aston Way, Midpoint 18 Business Park, Middlewich, Cheshire, CW10 0HS

Description

Pennstat 885 is an anti-static agent based on an aqueous blend of surfactants.

Applications

Pennstat 885 is formulated for use in a range of applications including commercial printing and textile manufacturing.

Product Features

Pennstat 885 is used in the treatment of surfaces to increase their ability to dissipate a charge. It is surface active and functions either by lubricating a surface against friction or by providing a relatively conductive path over a surface for the dissipation of a charge.

Method of Use

Pennstat 885 should be applied to the surface of a material, dosage will vary dependent upon the application and should be determined by trial.

Product Safety

A Safety Data Sheet compliant with EU 2015/830 is available for Pennstat 885 on request. It contains any safe handling guidelines that may be relevant to this product.

Storage, Shelf Life & Packaging

Pennstat 885 has a shelf life of 12 months when stored in original and unopened containers between 5°C and 30°C. It is available in 25kg, 200kg and 1,000kg packs.

Typical Properties

- Appearance: Blue liquid
- Solids: 4.0 – 6.00 %

Please note; these are typical properties only and should NOT be construed or used as a specification for this product.

Technical Support Contact Details

Telephone: +44 (0)1606 734820

Fax: +44 (0)1606 837867

Email: info@pennwhite.co.uk

Website: www.pennwhiteprint.co.uk